

334 Controller Cabinet

Standard Features

- Meets all Caltrans and FHWA requirements
- 3 vehicle phase operation
- 9 AC switched outputs
- 14 isolated inputs
- 2 or 4 channel detector modules can be used (loop, magnetometer or magnetic)
- Detector input panel with terminal blocks (Option A) or panduit ducts (Option B)
- Combined PDA-3 power distribution assembly and Model 206 24V DC plug-in power supply
- Sufficient space for two 170 controllers
- Removable, free standing 19" EIA rack assembly



Common Optional Features

- Fluorescent cabinet light(s) with door switch(es)
- Dual fans
- Communications panels
- External modems
- Pull-out drawer/shelf assembly
- Cabinet diagnostic kit
- Special configurations available
- 208 watch dog monitor
- Additional input files
- Police panel with lights on/off & auto/flash switches
- Underwriter's Laboratory Listing

Material	Aluminum (0.125" thick)
Finishes	Natural, Painted, Anodized
Dimensions	66" H x 24" W x 30" D
Mounting	Base Mounted, Bolt Pattern 25" x 15" (4) 3/4" x 16" Anchor Bolts (optional)
Access	Full size doors, front and back
Ventilation	100 CFM Fan with Thermostatic Control Filtered air intake in front door
Lock System	3 point, choice of Corbin or Best locks
Handles	Stainless steel with padlock feature
Door Stops	90° & 180° stop, each door, top & bottom ($\pm 10^\circ$)
Rack Assembly	Removable, Standard, 19" EIA Rack, with: <ul style="list-style-type: none"> (1) Controller Shelf (1) Input file (1) Model PDA-3 Combined Power Supply & Power Distribution Assembly (1) Service Panel (1) Fan & Thermostat Assembly

Note: Standard subassemblies assure interchangeability between manufacturers.

Shipping Wt. 200 lbs., without plug-ins or Model 170 Controller

McCain reserves the right to change product specifications without notice. McCain 3/07